



SAFETY DATA SHEET

DIS-SPRAY

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME DIS-SPRAY
 PRODUCT NO. 505031
 APPLICATION Embalming Spray
 SUPPLIER Dodge Company Ltd,
 Units 11/15 Ardglen Industrial Estate,
 Whitchurch, Hampshire,
 RG28 7BB, United Kingdom
 44 (0)1256-893883
 44 (0)1256-893868

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
FORMALDEHYDE ...%	200-001-8	50-00-0	1-5%	Carc3;R40 T;R23/24/25 C;R34 R43
METHANOL	200-659-6	67-56-1	< 1%	F;R11 T;R23/24/25,R39/23/24/25
PROPAN-2-OL	200-661-7	67-63-0	60-100%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Highly flammable. Irritating to eyes. Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. Vapours may cause drowsiness and dizziness.

CLASSIFICATION Carc 3;R40. Xi;R36. R43. F;R11. R67.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. Get medical attention. NOTE! Keep affected person away from heat, sparks and flames!

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water for several minutes. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

May ignite if strongly heated.

SPECIFIC HAZARDS

Fire creates: Toxic gases/vapours/fumes of Carbon monoxide (CO). Carbon dioxide (CO2).

DIS-SPRAY

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not contaminate water sources or sewer. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Container must be kept tightly closed. Use explosion proof electric equipment.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep in original container.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
METHANOL	OES	200 ppm(Sk)	266 mg/m3(Sk)	250 ppm(Sk)	333 mg/m3(Sk)
PROPAN-2-OL	OES	400 ppm	999 mg/m3	500 ppm	1250 mg/m3
FORMALDEHYDE ...%	MEL	2 ppm	2.5 mg/m3	2 ppm	2.5 mg/m3

INGREDIENT COMMENTS

MEL = Maximum Exposure Limit. OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear Liquid	RELATIVE DENSITY	.860-.880 @ 20 °c
COLOUR	Blue	VAPOUR PRESSURE	33 mmHg @ 20 °c
ODOUR	Mild (or faint). Odour of alcohol	VOLATILE BY VOL. (%)	99.6
SOLUBILITY	Soluble in water	FLAMMABILITY LIMIT - LOWER(%)	2
BOILING POINT (°C)	75-77 760 mm Hg		
VAPOUR DENSITY (air=1)	>1		
EVAPORATION RATE	>1 BuAc=1		
FLASH POINT (°C)	11-13 CC (Closed cup).		
FLAMMABILITY LIMIT - UPPER(%)	12		

10 STABILITY AND REACTIVITY

DIS-SPRAY**STABILITY**

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong reducing agents.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION**INHALATION**

Prolonged inhalation of high concentrations may damage respiratory system.

INGESTION

May cause stomach pain or vomiting. Swallowing concentrated chemical may cause severe internal injury.

SKIN CONTACT

May cause sensitisation by skin contact. Prolonged contact may cause dryness of the skin.

EYE CONTACT

Vapour, spray or dust may cause chronic eye irritation or eye damage.

HEALTH WARNINGS

INHALATION. May cause irritation to the respiratory system. **SKIN CONTACT.** Acts as a defatting agent on skin. May cause cracking of skin, and eczema. **EYE CONTACT.** May cause severe irritation to eyes. **INGESTION.** May cause stomach pain or vomiting.

Other Health Effects

Carcinogen Category 3.

MEDICAL CONSIDERATIONS

Allergies. Skin disorders and allergies.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not known.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UK ROAD CLASS	3		
PROPER SHIPPING NAME	FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL, METHANOL)		
UN NO. ROAD	1993	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	HAZARD No. (ADR)	33
ADR LABEL NO.	3	HAZCHEM CODE	3YE
CEFIC TEC(R) NO.	30GF1-I+II,30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1993
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	II	EMS	F-E, S-E
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1993	ICAO CLASS	3
AIR PACK GR.	II		

DIS-SPRAY**15 REGULATORY INFORMATION**

LABELLING



Harmful



Highly Flammable

CONTAINS

FORMALDEHYDE ...%

RISK PHRASES

R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R67	Vapours may cause drowsiness and dizziness.
R11	Highly flammable.
R36	Irritating to eyes.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51	Use only in well-ventilated areas.
S36/37	Wear suitable protective clothing and gloves.
S60	This material and its container must be disposed of as hazardous waste.

UK REGULATORY REFERENCES

Highly Flammable Liquid Regulations 1972. Petroleum (Consolidation) Act, as amended 1984 SI 1244.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EEC. System of specific information relating to Dangerous Preparations. 2001/58/EEC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Occupational Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al.

REVISION DATE OCTOBER 2004

SAFETY DATA SHEET STATUS

Approved.

RISK PHRASES IN FULL

R11	Highly flammable.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R67	Vapours may cause drowsiness and dizziness.

DIS-SPRAY
DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.