

**MATERIAL SAFETY DATA SHEET**

**I. PRODUCT IDENTIFICATION:**

Trade Name.....: **PLASDO 25**

Class.....: Arterial Embalming Chemical, Mixture

DOT/UN Hazard Classification: Other Regulated Substances, Liquid, NOS (Contains Formaldehyde), 9, NA 3082, PG III, Ltd. Qty.

**Manufacturer:** The Dodge Company, Inc.  
165 CambridgePark Drive  
Cambridge, MA 02140-2388  
(617) 661-0500

**Hazard Rating:** FIRE..... 2      4 = Extreme  
HEALTH..... 3      3 = High  
REACTIVITY..... 0      2 = Moderate  
SPECIAL..... 0      1 = Slight  
0 = No Hazard

**II. HAZARDOUS INGREDIENTS:**

<u>Common Name</u>	<u>Chemical Family</u>	<u>CAS#</u>	<u>Wt %</u>	<u>Exposure Limit</u>
Formaldehyde	Aldehyde	50-00-0	24	0.75 ppm (OSHA TWA); 0.3 ppm Ceiling (ACGIH) 2 ppm (OSHA STEL) Potential Cancer Hazard per NTP & OSHA Suspected Human Carcinogen per ACGIH Known carcinogen per IARC
Methanol or Methyl Alcohol	Alcohol	67-56-1	8	200 ppm (OSHA TWA and ACGIH TLV-TWA)* 250 ppm (OSHA STEL and ACGIH TLV-STEEL)* *Includes Skin

**III. PHYSICAL DATA:**

Boiling Point (°F).....: 181-185 (83-85°C)      **Specific Gravity (H<sub>2</sub>O=1)**.....: 1.060-1.070  
 Vapor Pressure (mm Hg): Unknown      **Percent Volatile (by volume)**.....: 96  
 Vapor Density (Air=1)....: Greater than 1      **Evaporation Rate (Bu Acetate=1):** Less than 1  
 Solubility in Water.....: Complete      **pH**.....: 8.5-9.5

**Appearance and Odor:** Orange-pink opaque liquid, slightly perfumed, with a pungent odor.

**IV. FIRE AND EXPLOSION HAZARD DATA:**

**Flammable Limits in Air:** 7%-73%\*      **Flash Point:** 144-148°F (62-64°C)  
 \*For solutions of 37% formaldehyde and 7-15% methanol.

**Extinguishing Media:** Water spray, foam, dry chemical, or carbon dioxide.

**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus (SCBA) and complete personal protective equipment.

**Unusual Fire and Explosion Hazards:** Water streams may splash and spread flaming liquid.

**V. REACTIVITY DATA:**

**Stability:** Stable.      **Hazardous Polymerization:** Will not occur.

**Conditions to Avoid:** Exposure to cold may cause increased cloudiness and precipitation of polymers that will slowly re-dissolve upon gentle heating.

**Incompatibility (materials to avoid):** Avoid contact with strong oxidizers, strong alkalis, strong mineral acids, and phenol.

**Hazardous Decomposition Products:** May form formaldehyde gas, carbon dioxide, carbon monoxide, and various hydrocarbons.

**MATERIAL SAFETY DATA SHEET**

**Name:** PLASDO 25

**VI. HEALTH HAZARD DATA:** Primary routes of entry: INHALATION, SKIN.

**Hazard Identification:**

**INHALATION:** Highly irritating to upper respiratory tract. May cause inflammation of lining of nose, throat, and lungs, with bronchopneumonia and edema possible from extremely irritating exposure. Can cause central nervous system depression.

**SKIN:** Contact with liquid causes drying, cracking, and scaling. Prolonged and repeated contact causes a hardening or tanning effect. May cause contact dermatitis or other allergic reactions.

**EYE CONTACT:** Exposure to high vapor concentrations or contact with liquid causes tearing and severe irritation. Contact with liquid causes severe burns.

**INGESTION:** Poisonous if swallowed. Causes severe irritation to mouth, throat, and stomach. Severe stomach pains will follow with possible loss of consciousness. Blindness or death may occur.

**Emergency and First Aid Procedures:**

**INHALATION:** Remove person from contaminated area. If breathing has stopped, give artificial respiration. If breathing is difficult, administer oxygen. Contact a physician.

**SKIN:** Remove contaminated clothing. Wash skin with large amounts of water. If irritation persists, contact a physician.

**EYE CONTACT:** Flush eyes with water for at least 15 minutes. Contact a physician immediately.

**INGESTION:** If the person is conscious, induce vomiting immediately by giving 2 glasses of water and pressing a finger down the throat. Repeat until vomit is clear, then give milk. Contact a physician immediately.

**VII. SAFE HANDLING AND USE:**

**Spill Procedures:** Eliminate ignition sources, and soak up the spill with noncombustible absorbent material. Neutralize with a diluted solution (<5%) of ammonia or sodium sulfite. Remove absorbent material to a chemical disposal area.

**Waste Disposal:** Improper disposal can cause damage to the environment. Dispose of all material in accordance with federal, state, and local regulations.

**VIII. SPECIAL PROTECTION INFORMATION:**

**Respiratory Protection:** A full-face shield/goggles combination or appropriate respirator, NIOSH/MSHA approved, should be used if exposure limits are exceeded. See Table 1, 29 CFR 1910.1048g.

**Protective Gloves:** Rubber, neoprene, nitrile, or other waterproof gloves.

**Eye Protection:** Safety goggles for normal use.

**Ventilation:** Local exhaust is recommended to stay below exposure limits.

**IX. SPECIAL PRECAUTIONS:**

**Handling and Storage:** Avoid contact with eyes, skin, and clothing. Avoid prolonged breathing of vapor. Do not store for long periods of time below 35°F (2°C) or above 110°F (43°C). Keep containers tightly closed when not in use. Wash thoroughly after handling.