

METAFLOW

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Provide good ventilation. Avoid inhalation of vapours.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
FORMALDEHYDE ...%	WEL	2 ppm	2.5 mg/m3	2 ppm	2.5 mg/m3
METHANOL	WEL	200 ppm(Sk)	266 mg/m3(Sk)	250 ppm(Sk)	333 mg/m3(Sk)
SODIUM HYDROXIDE	WEL				2 mg/m3

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Well-ventilated area.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use eye protection.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid Clear Light viscous		
COLOUR	Pink		
ODOUR	Mild (or faint). Spicy.		
SOLUBILITY	Soluble in water		
BOILING POINT (°C)	98-100 760 mm Hg	RELATIVE DENSITY	1.025-1.035 @ 20 °c
VAPOUR DENSITY (air=1)	>1	EVAPORATION RATE	<1 BuAc=1
VOLATILE BY VOL. (%)	96	pH-VALUE, CONC. SOLUTION	9.5-10.5
FLASH POINT (°C)	>93 CC (Closed cup).		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and alkalis. Avoid contact with strong oxidisers. Avoid contact with strong reducing agents.

11 TOXICOLOGICAL INFORMATION

METAFLOW

INHALATION

Harmful by inhalation. Prolonged inhalation of high concentrations may damage respiratory system. May cause irritation to the respiratory system. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

INGESTION

Harmful if swallowed. May cause discomfort if swallowed. May cause stomach pain or vomiting. Swallowing concentrated chemical may cause severe internal injury.

SKIN CONTACT

Harmful in contact with skin. Irritating to skin. May cause sensitisation by skin contact. Prolonged contact may cause dryness of the skin.

EYE CONTACT

Irritating to eyes. Risk of serious damage to eyes.

HEALTH WARNINGS

Prolonged inhalation of high concentrations may damage respiratory system. Prolonged or repeated exposure may cause severe irritation.

The product causes irritation of mucous membranes and may cause abdominal discomfort if swallowed.

MEDICAL CONSIDERATIONS

Allergies. Skin disorders and allergies. History of smoking.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not known.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

	No transport warning sign required.		
ADR CLASS	Not classified for transportation.	MARINE POLLUTANT	No.

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

S37 Wear suitable gloves.

P13 Safety data sheet available for professional user on request.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al.

REVISION DATE May 2007

METAFLOW

RISK PHRASES IN FULL

R11	Highly flammable.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R35	Causes severe burns.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.