SDS Revision Date:

02/04/2014



# 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Identity	Dry Wash II
Alternate Names	Chemical Mixture
1.2. Relevant identified uses of the sub	ostance or mixture and uses advised against
Intended use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.
1.3. Details of the supplier of the safety	y data sheet
Company Name	The Dodge Company, Inc
	9 Progress Road
	Billerica, MA 01821
Emergency	
CHEMTREC (USA)	(800) 424-9300
Customer Service	
The Dodge Company, Inc	(800) 443-6343, (978) 600-2099

## 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Acute Tox. 4;H302	Harmful if swallowed.
Acute Tox. 5;H313	May be harmful in contact with skin. (Not adopted by US OSHA)
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
STOT SE 2;H371	May cause damage to organs.
Aquatic Chronic 1;H410	Very toxic to aquatic life with long lasting effects.

SDS Revision Date:



#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H371b May cause damage to organs if inhaled or swallowed.

H371h May cause damage to organs in contact with skin.

H410 Very toxic to aquatic life with long lasting effects.

#### [Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

#### [Response]:

P301+312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P309+311 IF exposed or you feel unwell Call a POISON CENTER or doctor / physician.

P321 Specific treatment (see information on this label).

P330 Rinse mouth.

P337+313 If eye irritation persists: Get medical advice / attention.

SDS Revision Date:

02/04/2014



P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use alcohol resistant foam, CO2, powder, water spray for extinction. Do not use water jet. P391 Collect spillage.

#### [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

#### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
2-Propanone CAS Number: 0000067-64-1	25 - 50	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Heptane, branched cyclic CAS Number: 0426260-76-6	25 - 50	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
Acetic acid, 1-methylethyl ester CAS Number: 0000108-21-4	1.0 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Methanol CAS Number: 0000067-56-1	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

SDS Revision Date:

02/04/2014



### 4. First aid measures

#### 4.1. Description of first aid measures General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth. Irrigate copiously with clean fresh water for at least 15 minutes, holding the evelids apart Eves and seek medical attention. Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser. Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. 4.2. Most important symptoms and effects, both acute and delayed Overview Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details. Inhalation May cause damage to organs. Eyes Causes serious eye irritation. Skin May be harmful in contact with skin. (Not adopted by US OSHA) Causes skin irritation. Ingestion Harmful if swallowed.

SDS Revision Date:

02/04/2014



## 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sup>2</sup>, powder, water spray. Do not use; water jet.

#### 5.2. Special hazards arising from the substance or mixture

Carbon Monoxide and Carbon Dioxide

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

Do not breathe mist / vapors / spray.

#### 5.3. Advice for fire-fighters

Wear self-contained breathing apparatus to protect from decomposition products.

ERG Guide No. 128

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep container closed when not in use. Avoid contact with eyes, skin, or clothing.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Vapor is heavier than air and may flow along surface to distant ignition source and flashback. Spread an inert absorbent on the spill and place in a suitable, properly labeled container for recovery or disposal.

Flush area with large quantities of water.

SDS Revision Date:

02/04/2014



## 7. Handling and storage

#### 7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage. Incompatible materials: Strong oxidizing agents See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

#### Exposure

CAS No.	Ingestion	Source	Value
0000067-56-1	Methanol	OSHA	TWA 200 ppm (260 mg/m3)
		ACGIH	TWA: 200 ppmSTEL: 250 ppm Skin
		NIOSH	TWA 200 ppm (260 mg/m3) ST 250 ppm (325 mg/m3) [skin]
		Supplier	No Established Limit
0000067-64-1	2-Propanone	OSHA	TWA 1000 ppm (2400 mg/m3)STEL 2400 mg/m3
		ACGIH	TWA: 250 ppmSTEL: 500 ppm Skin
		NIOSH	250 ppm (590 mg/m3) TWA
		Supplier	No Established Limit
0000108-21-4	Acetic acid, 1-methylethyl ester	OSHA	TWA 250 ppm (950 mg/m3)
		ACGIH	TWA: 100 ppmSTEL: 200 ppm Revised 2003,
		NIOSH	no established RELs
		Supplier	No Established Limit

SDS Revision Date:

02/04/2014



0426260-76-6	Heptane, branched cyclic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

#### Carcinogen Data

CAS No.	Ingestion	Source	Value
0000067-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000067-64-1	2-Propanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-21-4	Acetic acid, 1-methylethyl ester	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0426260-76-6	Heptane, branched cyclic	OSHA	Select Carcinogen: No
			Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

#### 8.2. Exposure controls

Respiratory Eyes	Not necessary where area is properly ventilated. Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.
Skin	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Wear PVC or rubber gloves.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

SDS Revision Date:

02/04/2014



## 9. Physical and chemical properties

Appearance	Liquid
Odor	
Odor threshold	Not Me
рН	N.A
Melting point / freezing point (°C)	N.A
Initial boiling point and boiling range (°C)	59C 13
Flash Point	-19C -2
Evaporation rate (Ether = 1)	Greate
Flammability (solid, gas)	Not Ap
Upper/lower flammability or explosive limits	Lower
	Upper
Vapor pressure (Pa)	Not Me
Vapor Density	Greate

Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature (°C) Decomposition temperature Viscosity (cSt) VOC %

ot Measured .Α .Α 9C 138.2F 9C -2.2F TCC reater than 1 (Bu Acetate=1) ot Applicable ower Explosive Limit: 2.5% pper Explosive Limit: 12.8% ot Measured reater than 1 .78 @ 20C Miscible Not Measured Not Measured Not Measured Not Measured 100%

#### 9.2. Other information

No other relevant information.

### **10. Stability and reactivity**

10.1. Reactivity
Hazardous Polymerization will not occur.
10.2. Chemical stability
Stable under normal circumstances.
10.3. Possibility of hazardous reactions
No data available.

SDS Revision Date:

02/04/2014



10.4. Conditions to avoid
Excessive heat and open flame.
10.5. Incompatible materials
Strong oxidizing agents
10.6. Hazardous decomposition products
Carbon Monoxide and Carbon Dioxide

### 11. Toxicological information

#### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
2-Propanone - (67-64-1)	2,000.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	76.00, Rat - Category: NA	No data available	No data available
Heptane, branched cyclic - (426260-76-6)	No data available	No data available	No data available	No data available	No data available
Acetic acid, 1-methylethyl ester - (108-21-4)	6,750.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	17,129.60, Rabbit - Category: NA	No data available	No data available
Methanol - (67-56-1)	143.00, Human - Category: 3	15,800.00, Rabbit - Category: NA	128.00, Rat - Category: NA	No data available	64,000.00, Rat - Category: NA

SDS Revision Date:

02/04/2014



Item	Category	Hazard
Acute Toxicity (mouth)	4	Harmful if swallowed.
Acute Toxicity (skin)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute Toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)		Not Applicable
Sensitization (skin)		Not Applicable
Germ toxicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive Toxicity		Not Applicable
Specific target organ systemic toxicity (single exposure)	2	May cause damage to organs.
Specific target organ systemic Toxicity (repeated exposure)		Not Applicable
Aspiration hazard		Not Applicable

### **12. Ecological information**

#### 12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Very toxic to aquatic life with long lasting effects.

#### **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
2-Propanone - (67-64-1)	100.00, Pimephales promelas	10.00, Daphnia magna	20.565 (72 hr), Ulva pertusa
Heptane, branched cyclic - (426260-76-6)	Not Available	Not Available	Not Available
Acetic acid, 1-methylethyl ester - (108-21-4)	Not Available	Not Available	Not Available
Methanol - (67-56-1)	100.00, Pimephales promelas	10,000.00, Daphnia magna	16.912 (96 hr), Ulva pertusa

SDS Revision Date:

02/04/2014



#### 12.2. Persistence and degradability

There is no data available on the preparation itself. **12.3. Bioaccumulative potential** Not Measured **12.4. Mobility in soil** No data available. **12.5. Results of PBT and vPvB assessment** This product contains no PBT/vPvB chemicals. **12.6. Other adverse effects** No data available.

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

### **14. Transport information**

14.1. UN number

UN1993 Flammable liquids, n.o.s.,(contains Acetone/Heptane)

14.2. UN proper shipping name 14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

DOT Proper Shipping Flammable liquids, Name n.o.s.,(contains Acetone/Heptane)

#### IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name Flammable liquids, n.o.s.,(contains Acetone/Heptane)

**SDS Revision Date:** 

02/04/2014



DOT Hazard Class	3	IMDG Hazard Class	3
DOT Label	3	Sub Class	
UN / NA Number	UN1993		
DOT Packing Group	II	IMDG Packing Group	П
CERCLA/DOT RQ	1280 gal. / 10661 lbs.		

14.4. Packing group

Ш

14.5. Environmental hazards

IMDG Marine Pollutant: (Heptane, branched cyclic)

#### 14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

### 15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.
WHMIS Classification	B2 D2B

**US EPA Tier II Hazards** 

Fire: Yes Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs) (>0.1%) :

2-Propanone (5,000.00)

Methanol (5,000.00)

EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

Methanol

#### Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

SDS Revision Date:

02/04/2014



Proposition 65 - Developmental Toxins (>0.0%): (No Product Ingredients Listed)

#### Proposition 65 - Female Repro Toxins (>0.0%): (No Product Ingredients Listed)

#### Proposition 65 - Male Repro Toxins (>0.0%): (No Product Ingredients Listed)

#### N.J. RTK Substances (>1%) :

Acetic acid, 1-methylethyl ester

2-Propanone

Methanol

#### Penn RTK Substances (>1%) :

Acetic acid, 1-methylethyl ester

2-Propanone

Methanol

SDS Revision Date:

02/04/2014



### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

#### H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

- H331 Toxic if inhaled.
- H336 May cause drowsiness and dizziness.
- H370 Causes damage to organs.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### This is the first revision of this SDS format, changes from previous revision not applicable.

This Safety data Sheet was prepared using information provided by/obtained from the Dodge Chemical Company Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. The Dodge Chemical Company, Inc. expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of The Dodge Chemical Company, Inc.

End of Document