Safety Data Sheet Nail Varnish SDS Revision Date:

04/25/2014



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Product Identity Alternate Names

Nail Varnish Embalming Cosmetic, liquid tint mixture

1.2. Relevant identified uses of the substance or mixture and uses advised againstIntended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet Company Name

The Dodge Company, Inc 9 Progress Road Billerica, MA 01821

Emergency CHEMTREC (USA) Customer Service The Dodge Company, Inc

(800) 424-9300

(800) 443-6343, (978) 600-2099

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Acute Tox. 4;H302	Harmful if swallowed.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
Repr. 2;H361D	Suspected of damaging the unborn child.
STOT SE 3;H336	May cause drowsiness or dizziness.
STOT RE 2;H373	May cause damage to organs through prolonged or repeated exposure.

SDS Revision Date:

04/25/2014

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

SDS Revision Date:

04/25/2014



P330 Rinse mouth.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Toluene CAS Number: 0000108-88-3	25 - 50	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]
N-Butyl Acetate CAS Number: 0000123-86-4	25 - 50	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
sopropyl Alcohol CAS Number: 0000067-63-0	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Butanone CAS Number: 0000078-93-3	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Xylene CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

SDS Revision Date:

04/25/2014



4. First aid measures

4.1. Description of first	aid measures
General	Move victim to fresh air. Call 911 or emergency medical service if deemed necessary. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Remove and isolate contaminated clothing and shoes. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Wash skin with soap and water. In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean fresh water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove and isolate contaminated clothing and shoes. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Shower and wash with soap and water. Keep victim warm and quiet.
Ingestion	Do not induce vomiting, give plenty of water. Seek medical attention.
4.2. Most important sym	ptoms and effects, both acute and delayed
Overview	Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
	Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.
Skin	Causes skin irritation.
Ingestion	Harmful if swallowed.

SDS Revision Date:

04/25/2014



5. Fire-fighting measures

5.1. Extinguishing media

Use foam; extinguishing powder; dry chemicals; carbon dioxide Water may be ineffective. Water may be used to keep fire exposed containers cool.

5.2. Special hazards arising from the substance or mixture

Carbon Monoxide and Carbon Dioxide

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. Substance may be transported hot. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control or dilution water may cause pollution.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

SDS Revision Date:

04/25/2014



6.3. Methods and material for containment and cleaning up

Vapor is heavier than air and may flow along surface to distant ignition source and flashback.

Large Spill: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.

Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage. Incompatible materials: Strong oxidizing agents See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure			
CAS No.	Ingestion	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA	TWA 400 ppm (980 mg/m3)STEL 500 ppm
		ACGIH	TWA: 200 ppmSTEL: 400 ppm Revised 2003,
		NIOSH	TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)
		Supplier	No Established Limit
0000078-93-3	Butanone	OSHA	TWA 200 ppm (590 mg/m3)
		ACGIH	TWA: 50 ppmSTEL: 100 ppm
		NIOSH	TWA 200 ppm (590 mg/m3) ST 300 ppm (885 mg/m3)
		Supplier	No Established Limit

SDS Revision Date:

04/25/2014



0000108-88-3	Toluene	OSHA	TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak)STEL 150 ppm
		ACGIH	TWA: 20 ppmR
		NIOSH	TWA 100 ppm (375 mg/m3) ST 150 ppm (560 mg/m3)
		Supplier	No Established Limit
0000123-86-4	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m3
		ACGIH	TWA: 20 ppmS
		NIOSH	TWA 150 ppm (710 mg/m3) ST 200 ppm (950 mg/m3)
		Supplier	No Established Limit
0001330-20-7	Xylene	OSHA	STEL 150 ppm
		ACGIH	TWA: 100 ppmSTEL: 150 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingestion	Source	Value
0000067-63-0	000067-63-0 Isopropyl Alcohol		Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000078-93-3	Butanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-88-3 Toluene	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0000123-86-4	N-Butyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7 Xylene	Xylene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

8.2. Exposure controls

•	
Respiratory	Not necessary where area is properly ventilated.
Eyes	Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.
Skin	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Wear PVC or rubber gloves.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

SDS Revision Date:

04/25/2014



Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Odor Odor threshold pH Melting point / freezing point Initial boiling point and boiling range Flash Point Evaporation rate (Ether = 1) Flammability (solid, gas) Upper/lower flammability or explosive limits

Vapor pressure (Pa) Vapor Density Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature Decomposition temperature Viscosity (cSt) VOC % straw-colored Liquid Strong solvent Not Measured Not Measured Not Measured 129F (54C) 21F (-6C) Greater than Bu Acetate Not Applicable Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured Not Measured Greater than Air 0.940 Negligible Not Measured Not Measured Not Measured Not Measured 80

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur. **10.2. Chemical stability** Stable under normal circumstances.

SDS Revision Date:

04/25/2014



10.3. Possibility of hazardous reactions
No data available.
10.4. Conditions to avoid
Excessive heat and open flame.
10.5. Incompatible materials
Strong oxidizing agents
10.6. Hazardous decomposition products
Carbon Monoxide and Carbon Dioxide

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

2-butoxyethanol and its acetate are readily absorbed through the skin and will cause harmful effects on the blood.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available
N-Butyl Acetate - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available
Isopropyl Alcohol - (67-63-0)	4,710.00, Rat - Category: 5	12,800.00, Rat - Category: NA	72.60, Rat - Category: NA	No data available	No data available
Butanone - (78-93-3)	2,737.00, Rat - Category: 5	6,480.00, Rabbit - Category: NA	32.00, Mouse - Category: NA	No data available	No data available
Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available	20.00, Rat - Category: NA	5,000.00, Rat - Category: 4

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).





Item	Category	Hazard
Acute Toxicity (mouth)	4	Harmful if swallowed.
Acute Toxicity (skin)		Not Applicable
Acute Toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)		Not Applicable
Sensitization (skin)		Not Applicable
Germ toxicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive Toxicity	Not Defined	Suspected of damaging the unborn child.
Specific target organ systemic toxicity (single exposure)	3	May cause drowsiness or dizziness.
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard		Not Applicable

12. Ecological information

12.1. Toxicity

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Isopropyl Alcohol - (67-63-0)	1,400.00, Lepomis macrochirus	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus
Butanone - (78-93-3)	400.00, Cyprinodon variegatus	520.00, Daphnia magna	500.00 (96 hr), Skeletonema costatum
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales

12.2. Persistence and degradability

There is no data available on the preparation itself.

SDS Revision Date:

04/25/2014



12.3. Bioaccumulative potential Not Measured
12.4. Mobility in soil No data available.
12.5. Results of PBT and vPvB assessment This product contains no PBT/vPvB chemicals.
12.6. Other adverse effects No data available.

13. Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

14. Transport information

14.1. UN number 14.2. UN proper shipping name UN1993

Flammable liquids, n.o.s.,(Contains Toluene/MEK)

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

DOT Proper Shipping Name	UN1993, Flammable liquids, n.o.s.,(Contains Toluene/MEK), 3, III
DOT Hazard Class DOT Label	3 3
UN / NA Number	UN1993
DOT Packing Group	III
CERCLA/DOT RQ	273 gal. / 2273 lbs.

14.4. Packing group 14.5. Environmental hazards

IMDG Marine Pollutant: No

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name	Flammable liquids, n.o.s.,(Contains Toluene/MEK)
IMDG Hazard Class	3
Sub Class	Not Applicable

IMDG Packing Group

Ш

SDS Revision Date:

04/25/2014



14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.
WHMIS Classification	B2 D2A
US EPA Tier II Hazards	Fire: Yes
Sudden Release of Pressure: No	

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

Butanone (5,000.00)

N-Butyl Acetate (5,000.00)

Toluene (1,000.00)

Xylene (100.00)

EPCRA 302 Extremely Hazardous : (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:

Isopropyl Alcohol

Toluene

Xylene

Proposition 65 - Carcinogens (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

Toluene

Proposition 65 - Female Repro Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%): (No Product Ingredients Listed)

SDS Revision Date:

04/25/2014



N.J. RTK Substances (>1%) :

Butanone Isopropyl Alcohol N-Butyl Acetate Toluene **Xylene** Penn RTK Substances (>1%) : Butanone

Isopropyl Alcohol N-Butyl Acetate Toluene **Xylene**

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

SDS Revision Date:

04/25/2014



This is the first revision of this SDS format, changes from previous revision not applicable.

This Safety data Sheet was prepared using information provided by/obtained from the Dodge Chemical Company Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. The Dodge Chemical Company, Inc. expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of The Dodge Chemical Company, Inc.

End of Document