SDS Revision Date:

06/01/2016

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Identity	Formaldegone
Alternate Names	Formaldehyde Fume Supressant
1.2. Relevant identified uses of the substance or mixture and u	uses advised against
Intended use Application Method	Formaldehyde Fume Suppressant See Technical Data Sheet.
1.3. Details of the supplier of the safety data sheet	
Company Name	The Dodge Chemical Company (Canada) Ltd. 1265 Fewster Drive, 7n/Mississauga ON L4W1A2
Emergency	
CANUTEC	(888) 226-8832
Customer Service	
The Dodge Chemical Company Canada Ltd.	(800) 263-0863, (905) 625-0311

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Dodge

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Eye Irrit. 2;H319	Causes serious eye irritation.
STOT SE 3;H336	May cause drowsiness or dizziness.
Aquatic Chronic 3;H412	Harmful to aquatic life with long lasting effects.

SDS Revision Date:

Dodge

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H412 Harmful to aquatic life with long lasting effects.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking. P241 Use explosion-proof electrical / ventilating / light / equipment.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+378 In case of fire: Use alcohol resistant foam, CO2, powder, water spray for extinction. Do not use water jet. [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

SDS Revision Date:

06/01/2016

Dodge

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
2-Propanol CAS Number: 0000067-63-0	50 - 75	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
AMINO-2-ETHYL-1,3-PROPANEDIOL CAS Number: 0000115-70-8	10 - 25		[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give

anything by mouth to an unconscious person.

Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean fresh water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

SDS Revision Date:

06/01/2016



Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details. May cause drowsiness or dizziness.

InhalationMay cause drowsiness or dizzEyesCauses serious eye irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO², powder, water spray. Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Carbon Monoxide and Carbon Dioxide

Keep away from heat / sparks / open flames / hot surfaces - No smoking. Use explosion-proof electrical / ventilating / light / equipment. Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus to protect from decomposition products.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep container closed when not in use. Avoid contact with eyes, skin, or clothing.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Vapor is heavier than air and may flow along surface to distant ignition source and flashback.

Spread an inert absorbent on the spill and place in a suitable, properly labeled container for recovery or disposal.

Flush area with large quantities of water.

SDS Revision Date:

06/01/2016

Dodge

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage. Incompatible materials: Strong oxidizing agents See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingestion	Source	Value	
0000067-63-0	2-Propanol	OSHA	TWA 400 ppm (980 mg/m3)STEL 500 ppm	
		ACGIH	TWA: 200 ppmSTEL: 400 ppm Revised 2003,	
		NIOSH	TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)	
		Supplier	No Established Limit	
0000115-70-8	AMINO-2-ETHYL-1,3-PROPANEDIOL	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	No Established Limit	
		Supplier	No Established Limit	

Dodge

SDS Revision Date:

06/01/2016

Carcinogen Data

CAS No.	Ingestion	Source	Value	
0000067-63-0	2-Propanol	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0000115-70-8	AMINO-2-ETHYL-1,3-	OSHA	Select Carcinogen: No	
	PROPANEDIOL		Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

8.2. Exposure controls	
Respiratory	Not necessary where area is properly ventilated.
Eyes	Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.
Skin	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Wear PVC or rubber gloves.
Engineering Controls F	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices L	Jse good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Transparent, yellowish Liquid
Odor	Alcohol Odor
Odor threshold	Not Measured
рН	N.A
Melting point / freezing point (°C)	N.A
Initial boiling point and boiling range (°C)	83-85C 181-185F
Flash Point	8-11C 47-51F
Evaporation rate (Ether = 1)	Partial >1
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 2%

SDS Revision Date:

06/01/2016

Dodge

Vapor pressure (Pa) Vapor Density Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature (°C) Decomposition temperature Viscosity (cSt) VOC % Upper Explosive Limit: 12% 33 Greater than 1 (Bu Acetate=1) 0.845-0.890 Partial Not Measured Not Measured Not Measured Not Measured 100%

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity
Hazardous Polymerization will not occur.
10.2. Chemical stability
Stable under normal circumstances.
10.3. Possibility of hazardous reactions
No data available.
10.4. Conditions to avoid
Excessive heat and open flame.
10.5. Incompatible materials
Strong oxidizing agents
10.6. Hazardous decomposition products
Carbon Monoxide and Carbon Dioxide

SDS Revision Date:

06/01/2016

Dodge

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
2-Propanol - (67-63-0)	4,710.00, Rat -	12,800.00, Rat -	72.60, Rat -	No data	No data
	Category: 5	Category: NA	Category: NA	available	available
AMINO-2-ETHYL-1,3-PROPANEDIOL - (115-70-8)	No data	No data	No data	No data	No data
	available	available	available	available	available

Item	Category	Hazard
Acute Toxicity (mouth)		Not Applicable
Acute Toxicity (skin)		Not Applicable
Acute Toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)		Not Applicable
Sensitization (skin)		Not Applicable
Germ toxicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive Toxicity		Not Applicable
Specific target organ systemic toxicity (single exposure)	3	May cause drowsiness or dizziness.
Specific target organ systemic Toxicity (repeated exposure)		Not Applicable
Aspiration hazard		Not Applicable

Dodge

SDS Revision Date:

06/01/2016

12. Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
2-Propanol - (67-63-0)	1,400.00, Lepomis macrochirus	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus
AMINO-2-ETHYL-1,3-PROPANEDIOL - (115-70-8)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

SDS Revision Date:

06/01/2016

Dodge

13. Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

14. Transport information

14.1. UN number UN1993 14.2. UN proper shipping name Flammable liquids, n.o.s., (Contains Isopropanol) 14.3. Transport hazard class(es) **DOT (Domestic Surface Transportation)** IMO / IMDG (Ocean Transportation) **DOT Proper Shipping** Flammable liquids, **IMDG Proper** Flammable liquids, Name n.o.s.,(Contains **Shipping Name** n.o.s.,(Contains Isopropanol) Isopropanol) **DOT Hazard Class IMDG Hazard Class** 3 3 DOT Label 3 Sub Class **UN / NA Number** UN1993 DOT Packing Group Ш IMDG Packing Group || **CERCLA/DOT RQ** NA gal. / NA lbs. Ш 14.4. Packing group 14.5. Environmental hazards IMDG Marine Pollutant: 14.6. Special precautions for user Not Applicable 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

SDS Revision Date:

06/01/2016

Dodge

15. Regulatory information

Regulatory OverviewThe regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B

US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (>.1%) : (No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

2-Propanol

Proposition 65 - Carcinogens (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%): (No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

2-Propanol

Penn RTK Substances (>1%) :

2-Propanol

SDS Revision Date:

06/01/2016

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

Dodge

H336 May cause drowsiness and dizziness.

This is the first revision of this SDS format, changes from previous revision not applicable.

This Safety data Sheet was prepared using information provided by/obtained from The Dodge Chemical Company (Canada) Ltd. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. The Dodge Chemical Company (Canada) Ltd. expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of The Dodge Chemical Company (Canada) Ltd.